




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H04B 7/185	A1	(11) International Publication Number: WO 99/31821 (43) International Publication Date: 24 June 1999 (24.06.99)
(21) International Application Number: PCT/US98/23963 (22) International Filing Date: 10 November 1998 (10.11.98) (30) Priority Data: 08/989,622 12 December 1997 (12.12.97) US (71) Applicant: AT & T WIRELESS SERVICES, INC. [US/US]; 5000 Carillon Point, Kirkland, WA 98033 (US). (72) Inventors: IOAN, Leuca; 11123 N.E. 37th Court, Bellevue, WA 98004 (US). WEN-PING, Ying; 5591 179th Avenue, S.E., Bellevue, WA 98006 (US). (74) Agents: DWORETSKY, Samuel, H. et al.; AT & T Corp., P.O. Box 4110, Middletown, NJ 07748 (US).		(81) Designated States: CA, MX, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>With international search report.</i>

(54) Title: HIGH BANDWIDTH DELIVERY AND INTERNET ACCESS FOR AIRBORNE PASSENGERS

**(57) Abstract**

A method and a communications system in which a request for data transmitted by an airborne transmitter over a low-bandwidth air-to-ground communication system uplink and received by a ground-based receiver. The requested data is then transmitted over a high-bandwidth communication system downlink, such as a DBS satellite system downlink, preferably using an MPEG-2 compression technique, and received by an airborne receiver located on the same aircraft as the airborne transmitter. The received request for data is transmitted to a data network that contains the requested data, such as the Internet or a private data network, using circuit-switched techniques. According to the invention, the requested data includes one of video information, audio information and textual information.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece	ML	Mali	TR	Turkey
BG	Bulgaria	HU	Hungary	MN	Mongolia	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MR	Mauritania	UA	Ukraine
BR	Brazil	IL	Israel	MW	Malawi	UG	Uganda
BY	Belarus	IS	Iceland	MX	Mexico	US	United States of America
CA	Canada	IT	Italy	NE	Niger	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NL	Netherlands	VN	Viet Nam
CG	Congo	KE	Kenya	NO	Norway	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NZ	New Zealand	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	PL	Poland		
CM	Cameroon	KR	Republic of Korea	PT	Portugal		
CN	China	KZ	Kazakstan	RO	Romania		
CU	Cuba	LC	Saint Lucia	RU	Russian Federation		
CZ	Czech Republic	LI	Liechtenstein	SD	Sudan		
DE	Germany	LK	Sri Lanka	SE	Sweden		
DK	Denmark	LR	Liberia	SG	Singapore		
EE	Estonia						

**HIGH BANDWIDTH DELIVERY AND INTERNET ACCESS
FOR AIRBORNE PASSENGERS**

CROSS REFERENCE TO RELATED APPLICATIONS

5 The present application is related to copending application Serial Number (Attorney Docket LEUCA 2-7), filed concurrently, and commonly assigned with the present invention.

BACKGROUND OF THE INVENTION

10 **1. Field of the Invention**

 The present invention relates to the field of telecommunications. More particularly, the present invention relates to a method and to a system for communicating between an airborne data terminal and a ground-based computer network.

15 **2. Description of Related Art**

 The ability for passengers on a commercial airline flight to make phone calls is well-known. Initially, such airborne telephone calls utilized an analog technology that was similar to that used by an airborne radio station broadcasting a modulated voice signal over a
20 designated frequency to a ground-based station. The ground station interfaced with a Public Switched Telephony Network (PSTN) to complete the call. The analog approach suffers from problems

associated with signal degradation, and requires a relatively large bandwidth for carrying a voice band signal.

An all digital air-to-ground telephony network service was introduced in 1993 in which voice signals are carried by an ISDN
5 link on an aircraft to a radio link. Modern digital transmission and speech processing techniques are used on the voice signals before an airborne radio transmitter transmits an encoded digital voice signal to the ground where the voice signal is routed to the PSTN. The digital approach delivers a clearer voice quality than the analog approach, and
10 allows evolving speech encoding techniques to carry more simultaneous voice calls over available communication channels.

At the time the all digital air-to-ground service was introduced, the only data service envisioned was facsimile and data modem-type calls to be made to ground-based stations or terminals.
15 To accommodate existing facsimile and data modems that might be used on an aircraft for sending facsimile documents or for retrieving e-mail messages, a voice encoder on the aircraft used for voice calls is bypassed with a proper rate adaptation so that modem signals are send over the radio link. Still, this type of connection is considered to be a
20 circuit-switched voice call, that is, each dialup consumes one standard voice channel. As a result, the tariff for a conventional airborne data

service call is the same as the tariff for a standard voice call because the procedure for setting up the two types of calls is the same, and the bandwidth that is consumed by a conventional airborne data call is the same as the bandwidth consumed by a standard voice call. Further, the types of data services that are conveniently available through conventional airborne data service calls are severely limited because of the limited bandwidth available for a conventional airborne data call. For example, conventional airborne data services do not provide a bandwidth that is sufficient for supporting, for example, access to the Internet in which graphics, audio, video, textual and multimedia content are available.

What is needed is a way to provide an integrated voice/data service to airborne passengers that can mix various data services, such as accessing the Internet or placing a voice call, and thereby utilize the limited air channels available to airborne passengers more efficiently.

SUMMARY OF THE INVENTION

The present invention provides a method and a communications system that provides an integrated voice/data service to airborne passengers that can mix various data services, such as

accessing the Internet or placing a voice call, and thereby efficiently utilizing the air channels available to airborne passengers.

The advantages of the present invention are provided by a method and a communications system in which a request for data

5 transmitted by an airborne transmitter over a low-bandwidth air-to-ground communication system uplink and received by a ground-based receiver. The requested data is then transmitted over a high-bandwidth communication system downlink, such as a DBS satellite system downlink, preferably using an MPEG-2 compression technique, and

10 received by an airborne receiver located on the same aircraft as the airborne transmitter. The received request for data is transmitted to a data network that contains the requested data, such as the Internet or a private data network, using circuit-switched techniques. The requests from all active data users are multiplexed on the same circuit-switched

15 channel, thus conserving the bandwidth for normal voice channels.

According to the invention, the requested data includes one of video information, audio information and textual information.

BRIEF DESCRIPTION OF THE DRAWINGS

The present invention is illustrated by way of example and not limitation in the accompanying figures in which like reference numerals indicate similar elements and in which:

Figure 1 shows a schematic block diagram of a
5 telecommunications system that provides an air-to-ground communication link between an airborne telecommunication data terminal and a ground-based network according to the present invention; and

Figure 2 is a diagram of a preferred configuration of a
10 telecommunications system providing an NATS-type packet data network uplink and a DBS-type system downlink according to the present invention.

DETAILED DESCRIPTION

The present invention provides a method and a system providing two-way data communications between an airborne data terminal station, such as a personal computer (PC) or a laptop computer, and a ground-based data network, such as the Internet, using a packet data switching technology. As a result, the present invention utilizes available air-to-ground bandwidth more efficiently than conventional airborne data telecommunications systems because the same air-to-ground channel is used for multiplexing data packets from different concurrent user data sessions.

Figure 1 shows a schematic block diagram of a telecommunications system 10 that provides an air-to-ground communication link between an airborne data terminal 11, such as a PC or a laptop computer, and a ground-based network 2, such as the Internet. According to the invention, system 10 is located on an airborne platform, such as an airplane, a helicopter or a space vehicle, and includes a data transport mechanism, a data server mechanism and an Application Programming Interface (API) function. The API function is used by an external application for interacting with the data server mechanism for call control functions and for performing

Operation, Administration, Maintenance and Provisioning (OAM&P) functions.

The data transport mechanism provides interfaces to and includes various data pipes that are both internal and external to the aircraft. The internal data pipes link passengers and aircraft personnel to a data server. According to the invention, the internal data pipes can be any of an existing Cabin Distribution System (CDS) using an Integrated Services Digital Network (ISDN), a Local Area Network (LAN), an Ethernet or a Fiber Distributed Data Interface (FDDI) network, and/or an Asynchronous Transmission Mode (ATM) network for distributing video, voice/audio, and textual data signals to a display screen located, for example, on the back of passenger seats. Preferably, an ATM internal data pipe uses an embedded open standard Operating System, such as JAVA.

The external pipes can be various wireless pipes, or air links, to a ground-based station or gateway, or to a satellite system. According to the invention, the different external pipes that can be used with the present invention can be an existing terrestrial link system, such as the North American Terrestrial System (NATS) or the European Terrestrial Flight Telephone System (TFTS), a direct air link to a terrestrial gateway, a link to a Low Earth Orbit (LEO) and/or a

Medium Earth Orbit (MEO) satellite system, and/or a link to one of the emerging broadband Satellite-based systems, such as the Digital Broadcast Satellite (DBS) or Teledesic systems.

In Figure 1, system 10 includes a plurality of airborne
5 data terminals 11, each of which are connected to a data server 12 by an internal data pipe 13, such as an Ethernet, in a well-known manner. Data terminals 11 can be data terminals 11a, 11b and 11c that are used by flight crew and personnel and data terminals 11e, 11f and 11g that are used by passengers. For example, data terminal 11a is located on
10 the flight deck of the aircraft, while data terminals 11b and 11c are located elsewhere in the aircraft and are used by a maintenance crew and/or members of the flight crew not located on the flight deck. Data terminals 11d, 11e and 11f are dedicated data terminals provided on-board the aircraft for the convenience of passengers and/or can be
15 portable or laptop computers provided by passengers.

Data server 12 acts as an intelligent airborne gateway and performs multiplexing and necessary call control functions. More specifically, data server 12 provides three general functions: 1) controlling various data transport interfaces; 2) multiplexing, routing,
20 and priority queuing functions for data packets; and 3) updating and maintaining various databases depending on the application as an off-

line process and for providing a uniform user interface capability (API) to client applications. Examples of off-line processes provided by data server 12 are a HyperText Transport Protocol (HTTP) process that provides an interface for Web browsing and an Aircraft Condition
5 Monitoring System (ACMS) process for collecting aircraft flight data for OA&M purposes.

Data server 12 preferably includes a network interface circuit (NIC) 14, a router 15, a database 16, and at least one and preferably a plurality of data transport interface circuits 17-20.

10 Network interface circuit 14 connects data server 12 to internal data pipe 13 in a well-known manner, and provides data packets received from data pipe 13 to router 15. Router 15 uses a routing table that is stored in routing table database 16 for directing data packets received from terminals 11a-11f and voice packets from telephones (not shown)
15 to an appropriate data transport interface circuit 17-20 based on a requested data service for subsequent transmission to a particular bearer service. The components forming data server 12 can be physically enclosed within one housing or enclosure, or can be physically located in separate housings that are distributed around the
20 aircraft depending on the technology used, the applications, and the physical constraints of the aircraft.

In Figure 1, gate link interface circuit 17 provides well-known interface functions for an air link through an antenna 21 directly to a ground-based gateway 22. Gateway 22 is connected to data network 2, such as the Internet. Similarly, Satellite Interface Circuit 5 (SIC) 18 provides well-known interface functions for an air link through an antenna 23 to a satellite network 24, such as an LEO or MEO satellite system. Satellite network 24 is connected to data network 2 through a ground station 24a that is a part of network 24. Exemplary satellite networks suitable for satellite network 24 include 10 several LEO/MEO systems that are designed primarily for voice service, such as the Iridium, Globalstar, ICO and Odyssey systems. The data service provided by these exemplary satellite systems is supported only as a supplementary service having a bit rate between 1.2 to 9.6 Kbps using voice band modem signaling similar to the 15 conventional two-way data services available from the NATS, TFTS and SATCOM.

NATS interface circuit 19 provides well-known interface functions for an air link through an Aircraft Communication Unit (ACU) 496 NATS unit 25 and an antenna 26 to a gateway 27 of an 20 NATS-type system 31, such as AT&T's NATS network. NATS-type system 31 is connected to data network 2 using a packet data transport

mechanism. The AT&T's NATS network includes approximately 150 ground stations covering the entire continental United States and parts of the Canada and Mexico. All NATS ground stations are interconnected to a switching center located in New Jersey from where

5 voice traffic is routed to a PSTN. The NATS ground stations are also interconnected through a frame relay network to data centers, or gateways, where the data packets are routed to a private data network or to public data network 2, such as the Internet. Using a modern protocol, such as MPP combined with PPTP or L2TP, the NATS

10 network supports an aggregated dynamic bandwidth of up to 290 Kbps in a channel block of 29 channels, subject to channel availability.

DBS decoder interface circuit 20 provides well-known interface functions for an air link through an antenna 28 to a DBS satellite system 29. DBS satellite system 29 is connected to data

15 network 2. The broadband satellite systems, such as the Geo-synchronous Earth Orbit (GEO) Digital Broadcast Satellite (DBS), are envisioned as providing a one-way data service as the primary service.

DBS technology uses an MPEG-2 digital compression system for sending a plurality of channels of digitized video signals through one

20 transponder. The MPEG-2 digital compression system can be used for multiplexing any digital signal, including a packet data signal, and for

intermixing a digital signal with a video signal for satellite broadcasting. From the point of view of the DBS system is concerned, there is no difference whether a transported signal is a compressed video signal or a sequence of IP packets.

5 Antenna 28 used on the aircraft must be a moving or a phased-array antenna for maintaining a line-of-sight with a transmitting satellite because DBS system is a GEO satellite system. An antenna of this type is relatively more costly than a standard fixed antenna. For other satellite systems, such as the Low Earth Orbit (LEO) satellites
10 that are not geo-synchronous, the satellite system handles handoffs, therefore, eliminating the need for a moving-type antenna for antenna
23.

To provide an interactive airborne data service, such as e-mail retrieval or Web browsing, the present invention uses an NATS-
15 type packet data network, such as the AT&T NATS, for an uplink data pipe and a DBS-type system for a downlink data pipe. For a typical application, the relative size, or bandwidth requirement, of the data request is small, while the amount of data returned in response to the request is relatively large. The capability of the NATS link is
20 sufficient for carrying a request for data, but is insufficient for carrying the requested data. Alternatively, the uplink data pipe can be through

an LEO/MEO satellite network 24, with the downlink data pipe being through DBS-type system 29.

Figure 2 is a diagram of a preferred configuration of a telecommunications system providing an NATS-type packet data network uplink data pipe and a DBS-type system downlink data pipe according to the present invention. System 10 uses an MPP technique that aggregates multiple on-demand 9.6 Kbps bandwidth upstream links from aircraft 40 to NATS system 31. Downstream links in excess of 5 Mbps bandwidth from the network are provided through the DBS system to the aircraft. IP packets are encapsulated by lower layer protocols so that there is a transparent conduit for IP packets to be transported from the aircraft to a desired host and from a host to the aircraft via a DBS link.

In Figure 2, a user using a laptop computer on airplane 40 that is connected to system 10 sends an uplink data request for establishing a high-speed data session through NATS system 31. The request is sent through a second gateway 32 to a desired access management server 33. After a proper authentication process and channel assignment, access management server 33 sends a service initiation acknowledgement message to the laptop computer via NATS system 31 and terrestrial gateway 27. The laptop computer receives

the service initiation acknowledgement message via NATS interface circuit 19, router 15 and internal data pipe 13 (Figure 1). The laptop computer sends a request to a particular website on Internet 2 via NATS system 31. The desired website responds to the data request by
5 sending the data requested to an access management server 33 that is connected to a DBS system 29. The requested data is transmitted from a ground station 29a to DBS satellite 29b, then to aircraft 40. The laptop computer receives the requested data from DBS interface circuit 20, router 15 and internal data pipe 13.

10 System 10 utilizes the advantages of the data compression features of DBS system 29 when downloading broadband data from a DBS satellite. An exemplary application that can be utilized by a flight crew is software downloading, flight information updates, etc. In-Flight Entertainment (IFE) services offered by an
15 airline can receive real-time video programs from a direct television-type service, or by allowing passengers to browse the Internet with ample bandwidth.

 Presently, the available DBS systems are broadcast-only systems. When a two-way DBS satellite link is available, data server
20 12 will treat such an uplink as another bearer service and uses the satellite broadband network for interconnecting aircraft 40 to a ground-

based gateway. The bandwidth available with the two-way broadband
satellite systems supports applications, such as video conferencing,
high-quality video, high-speed Internet, and virtual LAN to the
aircraft. An added advantage of using any of satellite systems 24, 29 is
5 that universal access is possible so that the same system can be used
anywhere on earth. For this embodiment of the present invention, the
satellite network is connected to the mobile terminal on-board the
aircraft, handling routing and handoffs needed for linking the mobile
terminal on-board the aircraft to a ground-based gateway in a well-
10 known manner similar to that used by conventional cellular telephone
system, instead of a network of ground stations that connect the
gateway. As long as an aircraft and a gateway can connect by way of a
satellite network, SVCs or PVCs can be set up between any pair of
terminal stations. For example, one aircraft can have an SVC to
15 another aircraft as long as both aircraft are serviced by the satellite
system. Similarly, an aircraft can have an SVC to any gateway as long
as both can be connected through the satellite system.

The API function of the present invention is provided by
a collection of APIs or procedures having a standardized execution
20 environment, and can be executed by applications, whether local or
remote, for allowing the configuration of call/data routes, monitoring

and reporting of activities, and messaging and presentation of data to users. An example of an API that can be used with the present invention are JAVA applets that can be executed by any JAVA-capable Web browser for allowing a flight crew to view the latest gate link
5 information or for ground control personnel to view the vital statistics of the aircraft in real time.

The API function of the present invention is the enabling tool for allowing quick introduction of new applications and/or services, for developing specific applications for call monitoring and
10 control purposes, and for incorporating new technologies without significant development effort. The APIs used with the present invention are highly modularized so that any combination of APIs can be incorporated into creating new applications without having impact on existing applications.

15 Preferably, the present invention uses the TCP/IP protocol as a networking protocol, thus allowing interconnection to virtually any network. An additional advantage of the present invention is that the ability to access to the vast collection of TCP/IP protocols, tools and applications provides the present invention with
20 the flexibility to meet the needs of future aircraft data services. The present invention is expandable by providing an infrastructure that is

modularized and is designed to use Open System interfaces, allowing new hardware and technologies to be incorporated with minimal development. Preferably, the present invention uses COTS hardware and software.

THE CLAIMS

What is claimed is:

1. A method for communicating data, the method comprising the steps of:

5 receiving a request for data over a low-bandwidth air-to-ground communication system uplink; and

transmitting the requested data over a high-bandwidth communication system downlink.

10 2. The method according to claim 1, wherein the high-bandwidth communication system downlink is a satellite downlink.

3. The method according to claim 2, wherein the satellite system downlink is part of a DBS satellite system.

15

4. The method according to claim 2, further comprising the step of transmitting the received request for data to a data network for obtaining the requested data, the data network containing the requested data.

20

5. The method according to claim 4, wherein the data network is the Internet.

6. The method according to claim 4, wherein the data network is a private network.

7. The method according to claim 4, further comprising the steps of:

transmitting the request for data from an airborne transmitter; and

receiving the requested data over the high-bandwidth communication system link by an airborne receiver, the airborne transmitter and the airborne receiver being on the same aircraft.

8. The method according to claim 7, wherein the step of transmitting the received request for data to the data network includes the step of using circuit-switched techniques for transmitting the received request for data to the data network.

9. The method according to claim 8, wherein the step of transmitting the requested data over the high-bandwidth communication

system downlink includes the step of using an MPEG-2 compression technique for transmitting the requested data over the high-bandwidth communication system downlink.

5 10. The method according to claim 4, wherein the requested data includes one of video information, audio information and textual information.

 11. A communications system, comprising:
10 a ground-based receiver receiving a request for data over a low-bandwidth air-to-ground communication system uplink;
 a transmitter transmitting the requested data over a high-bandwidth communication system downlink.

15 12. The system according to claim 11, wherein the high-bandwidth communication system downlink is a satellite downlink.

 13. The system according to claim 12, wherein the satellite system downlink is part of a DBS satellite system.

20

 14. The system according to claim 12, further comprising:

a data network containing the requested data; and
a bearer carrier system sending the received request for
data to the data network.

5 15. The system according to claim 14, wherein the data
network is the Internet.

16. The system according to claim 14, wherein the data
network is a private network.

10

17. The system according to claim 14, further comprising:
an airborne transmitter transmitting the request for data;
and

an airborne receiver receiving the requested data over
15 the high-bandwidth communication system link, the airborne
transmitter and the airborne receiver being on the same aircraft.

18. The system according to claim 17, further comprising a
circuit-switched communications network connected to the ground-
20 based receiver and the data network, the request for data received by


the ground-based receiver being sent to the data network over the circuit-switched communications network.

19. The system according to claim 18, wherein the DBS
5 satellite system uses an MPEG-2 compression technique for transmitting the requested data over the high-bandwidth communication system downlink.

20. The system according to claim 14, wherein the requested
10 data includes one of video information, audio information and textual information.


FIG. 1

1/2



THIS PAGE BLANK (USPTO)

2/2



THIS PAGE BLANK (USPTO)

INTERNATIONAL SEARCH REPORT

I. International Application No
PCT/US 98/23963

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 H04B7/185

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 H04B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	LOSQUADRO: "ABATE: Aeronautical Satellite Communications for Multimedia Services" IEE COLLOQUIUM ON EU'S INITIATIVES IN SATELLITE COMMUNICATIONS-MOBILE(REF. NO. 1997/087), 8 May 1997, pages 7/1-7/7, XP002096609 London, UK	1-7, 10-17; 20
Y	see the whole document	8, 9, 18, 19
Y	LOSQUADRO: "EuroSky Way: Multiregional Network for Satellite Multimedia" PROCEEDINGS OF FOURTH EUROPEAN CONFERENCE ON SATELLITE COMMUNICATIONS, 18 - 20 November 1997, XP002096610 Rome, Italy see abstract	8, 9, 18, 19

☒ Further documents are listed in the continuation of box C.

☐ Patent family members are listed in annex.

* Special categories of cited documents:

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

15 March 1999

Date of mailing of the international search report

31/03/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Felsen, J

INTERNATIONAL SEARCH REPORT

International Application No

PCT/US 98/23963

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	<p>LOSQUADRO: "SECOMS: Advanced Interactive Multimedia Satellite Communications for a variety of Compact Terminals"</p> <p>IEE COLLOQUIUM ON EU'S INITIATIVES IN SATELLITE COMMUNICATIONS-MOBILE (REF. NO. 1997/087), 8 May 1997, pages 3/1-3/7, XP002096611</p> <p>London, UK</p> <p>see the whole document</p> <p>-----</p>	<p>1-4, 6-8, 10-14, 16-18, 20</p>